

57 SERIES **UL - 718**

"ULTRA" BRAND ELECTROPERM LIGHT DUTY CHUCK (47 x 47 Quard Pole)





	-Pendent
B * * * * 9 · 9	Control Unit

- Work holding device for Milling machines.
- COLD DEVICE as it doesn't require power continuously except for short period of activation & deactivation.
- Suitable for light milling i.e. 1-3 mm depth of cut at recommended speed & feed.
- Maximum material removal is possible.
- Economical for operation & maintenance.
- No accidents due to power failure.
- Slippering force is 2.5 3 Kg/cm².
- Vertical Lifting Force is 35 40 Kg/cm².
- Variable supply unit to vary power which helps in alignment of jobs.
- Chuck is tested for Slippering force, Waterproof test, Temperature
- rise test, Electrical & Demagnetizing tests.
- Good quality & standard electrical accessories.

We also manufacture Special chucks to suit individual requirement.

Sr. No.	Cat No.	Size (mm)			
1.	UL - 71801	500L x 200 W x 80 H			
2.	UL - 71802	600L x 200 W x 80 H			
3.	UL - 71803	600L x 250 W x 80 H			
4.	UL - 71804	600L x 300 W x 80 H			
5.	UL - 71805	600L x 400 W x 80 H			
6.	UL - 71806	750L x 250 W x 90 H			

Sr. No.	Cat No.	Size (mm)				
7.	UL - 71807	750L	x 300 W	Х	90 H	
8.	UL - 71808	1000 L	x 250 W	Χ	90 H	
9.	UL - 71809	400 L	x 400 W	Х	90 H	
10.	UL - 71810	800 L	x 400 W	Χ	90 H	
11.	UL - 71811	1000 L	x 500 W	Χ	90 H	
12.	"ULTRA" CONT	ROL UN I T WI	ITH VARIAI	3LE	SUPPLY	
13.	"ULTRA" POLE EXTENSION BLOCK					
14.	SPECIAL "ULTR	A" POLE EXTI	ENSION BLO	OCK		
15.	"ULTRA" SPR I N	G POLE EXTE	NSION BLO	OCK		



Plain Pad



T Type Pad




E. P. M. Chuck with T Type Pad and T Nut



T Nut



Right angle pad



E. P. M. Chuck with Right angle pad